

RICOH IM 2702

✓ Copy ✓ Print ✓ Scan ✓ Fax



Intelligent and reliable

Bringing new intelligence to your document processes, this A3 black and white MFP has a colour touchscreen panel that simplifies operation and supports cloud integration.

Intelligent workflow tools

- Intuitive user interface
- Downloadable Smart apps
- Cloud integration
- Smartphone connection

The Smart Operation Panel plays host to a suite of intelligent workflow tools. Downloadable apps, such as ID Card Copy, automate time-consuming processes. Users can connect seamlessly to the MFP and print from / scan to their smartphones and tablets. And, with easy cloud integration, they can scan documents and upload them to cloud services, like DropBox™ and Sharepoint™.

Versatile and productive

- Fast 27 ppm print speed
- High capacity ARDF
- A6 to A3 paper formats
- 1600 sheet max capacity



The IM 2702 provides a versatile and productive answer to all document needs. It prints and copies in black and white, and scans in colour. Fax is an option. The ARDF quickly scans double-sided originals and multipage documents are printed at speed. With up to three 500 sheet paper trays and a multi-sheet bypass on line, it is easy to print onto different paper sizes or to feed envelopes and labels. And, with the MFP switching seamlessly between trays, there really is no need to stop.

Easy to maintain

- User installable MFP
- User replaceable Photo Conductor Unit
- Multiple language support
- High yield toner

Designed for use in demanding environments, the IM 2702 delivers robust performance with minimal support. Localisation is easy as the MFP supports a variety of languages, including Arabic. And, with pre-set developer and a user replaceable photo conductor unit, it can easily be installed and maintained by local staff. What is more, to ensure a fast return on the initial cost, the MFP's smart energy saving features and high yield toner cartridges reduce running costs.



RICOH IM 2702

MAIN SPECIFICATIONS

GENERAL

Warm-up time	25 seconds
First copy speed: BW	6.5 seconds
Continuous output speed	27 ppm
Memory: standard	2 GB
Memory: maximum	2 GB
ARDF capacity	sheets
Weight	46.5 kg
Dimensions: W x D x H	587 x 581 x 677 mm
Power source	220 - 240 V, 50 - 60 Hz
Laser classification	Class 1 Laser Product (IEC60825 - 1:2014)

COPIER

Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400%

PRINTER

Printer language	PCL5e PCL6 PostScript 3 (emulation)
Print resolution: maximum	600 x 600 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T USB2.0 Type B Wireless LAN (IEEE 802.11 a/b/g/n) USB Host 2.0
Mobile printing capability	Apple AirPrint Mopria® Google Cloud Print
Network protocol	TCP/IP (IP v4, IP v6)
Windows® environments	Windows® 7 Windows® 8.1 Windows® 10 Windows® Server 2008 Windows® Server 2008R2 Windows® Server 2012 Windows® Server 2012R2 Windows® Server 2016 Windows® Server 2019
Mac OS environments	Macintosh OS X v10.8 - v10.11

SCANNER

Scanning: B/W	50 ipm
Scanning: full colour	50 ipm
Resolution: maximum	1,200 dpi
Bundled drivers	Network TWAIN

FAX

Compatibility	ITU-T (CCITT) G3
Transmission speed	seconds
Modem speed: maximum	Kbps

PAPER HANDLING

Recommended paper size	Bypass tray Custom Size paper (Width: 90 mm - 305 mm, Length: 148 mm - 600 mm) Duplex tray
Paper input: standard	500 sheets
Paper input: maximum	1,600 sheets
Paper output: standard	250 sheets
Paper weight	Trays52 - 105 g/m² Bypass52 - 216 g/m²

ECOLOGY

Power consumption: max.	< 1,550 W
Power consumption operation: B&W	500 W

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet paper tray
2x 500-sheet paper tray
One-bin tray

RICOH IM 2702

MAIN SPECIFICATIONS

OTHER OPTIONS

- Fax unit
- Low cabinet
- Punch units
- PostScript 3
- IEEE 802.11 a/b/g/n
- OCR unit
- ADF handle
- NFC card reader
- Bypass tray cover
- Card reader cover
- Bridge unit



CONSUMABLES

Toner (regular yield)	4,000 prints
Toner (high yield)	prints
Consumable yield based on 2p/j	
6% coverage on A4	

Prodoc Svenska Kb

Bolmensvägen 43

121 22 Johanneshov

Sweden

08-602 06 02

www.prodoc.se